

Applicant : Erik Coelingh et al.
Appln. No. : 10/063,951
Page : 2

In the Claims:

This listing of claims will replace all prior versions and listings of claims in the application:

1. (currently amended) A method of controlling a vehicle comprising:
providing a driver subsystem and an active assist subsystem;
receiving at least one driver input into the driver subsystem from a driver of the vehicle;
outputting a driver output from the driver subsystem to the active assist subsystem, the driver output being derived from the at least one driver input;
providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;
providing a vehicle control and implementation subsystem; and
inputting an intended driving demand from the active assist program into the vehicle control and implementation subsystem;
wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation ~~system~~ subsystem come from the at least one driver input or the at least one active assist program.
2. (currently amended) ~~The method of controlling a vehicle of claim 1, further including:~~
A method of controlling a vehicle comprising:
providing a driver subsystem and an active assist subsystem;

receiving at least one driver input into the driver subsystem from a driver of the vehicle;

outputting a driver output from the driver subsystem to the active assist subsystem, the driver output being derived from the at least one driver input;

providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;

providing a vehicle control and implementation subsystem;

inputting an intended driving demand from the active assist program into the vehicle control and implementation subsystem;

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation subsystem come from the at least one driver input or the at least one active assist program; and

inputting environmental data into the active assist subsystem.

3. (original) The method of controlling a vehicle of claim 2, wherein:
the at least one active input is derived from the environmental data.

4. (currently amended) ~~The method of controlling a vehicle of claim 1, wherein:~~ A method of controlling a vehicle comprising:

providing a driver subsystem and an active assist subsystem;

receiving at least one driver input into the driver subsystem from a driver of the vehicle;

outputting a driver output from the driver subsystem to the active assist subsystem, the

driver output being derived from the at least one driver input;

providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;

providing a vehicle control and implementation subsystem; and
inputting an intended driving demand from the active assist program into the vehicle control and implementation subsystem;

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation subsystem come from the at least one driver input or the at least one active assist program; and

wherein the at least one active assist program includes an adaptive cruise control program.

5. (currently amended) ~~The method of controlling a vehicle of claim 1, wherein:~~ A method of controlling a vehicle comprising:

providing a driver subsystem and an active assist subsystem;
receiving at least one driver input into the driver subsystem from a driver of the vehicle;

outputting a driver output from the driver subsystem to the active assist subsystem, the driver output being derived from the at least one driver input;

providing at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input;

providing a vehicle control and implementation subsystem; and
inputting an intended driving demand from the active assist program into the vehicle
control and implementation subsystem;

wherein the intended driving demand is derived from a combination of the at least one
driver input and the at least one active input if the at least one active assist program is in the
on setting and if the driver of the vehicle does not overrule the at least one active assist
program, otherwise the intended driving demand is derived from the at least one driver input,
such that the vehicle control and implementation subsystem cannot determine if instructions for
the vehicle control and implementation subsystem come from the at least one driver input or
the at least one active assist program; and

wherein the at least one active assist program includes a collision mitigation program.

6. (original) The method of controlling a vehicle of claim 1, wherein:
the intended driving demand includes a longitudinal acceleration demand.
7. (original) The method of controlling a vehicle of claim 1, wherein:
the intended driving demand includes a longitudinal velocity demand.
8. (original) The method of controlling a vehicle of claim 1, wherein:
the intended driving demand includes a yaw rate demand.
9. (original) The method of controlling a vehicle of claim 1, wherein:
the intended driving demand includes a slip angle demand.
10. (original) The method of controlling a vehicle of claim 1, wherein:
the intended driving demand includes a wheel angle demand.
11. (currently amended) A vehicle control system comprising:
a driver subsystem receiving at least one driver input from a driver of the vehicle, the

Applicant : Erik Coelingh et al.
Appln. No. : 10/063,951
Page : 6

driver subsystem including a driver output outputting a driver output signal, the driver output signal being derived from the at least one driver input;

an active assist subsystem including an assist input receiving the driver output signal from the driver output of the driver subsystem, the active assist subsystem including at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input, the at least one active assist subsystem including an assist output;

a vehicle control and implementation subsystem having a control input receiving an intended driving demand from the assist output of the active assist program;

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation ~~system~~ subsystem come from the at least one driver input or the at least one active assist program.

12. (currently amended) ~~The vehicle control system of claim 11, wherein:~~ A vehicle control system comprising:

a driver subsystem receiving at least one driver input from a driver of the vehicle, the driver subsystem including a driver output outputting a driver output signal, the driver output signal being derived from the at least one driver input;

an active assist subsystem including an assist input receiving the driver output signal from the driver output of the driver subsystem, the active assist subsystem including at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input, the at least one active assist subsystem including an assist output;

Applicant : Erik Coelingh et al.
Appln. No. : 10/063,951
Page : 7

a vehicle control and implementation subsystem having a control input receiving an intended driving demand from the assist output of the active assist program;

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation come from the at least one driver input or the at least one active assist program; and

wherein the active assist subsystem receives environmental data.

13. (original) The vehicle control system of claim 12, wherein:
the at least one active input is derived from the environmental data.

14. (currently amended) ~~The vehicle control system of claim 11, wherein:~~ A vehicle control system comprising:

a driver subsystem receiving at least one driver input from a driver of the vehicle, the driver subsystem including a driver output outputting a driver output signal, the driver output signal being derived from the at least one driver input;

an active assist subsystem including an assist input receiving the driver output signal from the driver output of the driver subsystem, the active assist subsystem including at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input, the at least one active assist subsystem including an assist output;

a vehicle control and implementation subsystem having a control input receiving an intended driving demand from the assist output of the active assist program; _____

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the

Applicant : Erik Coelingh et al.
Appln. No. : 10/063,951
Page : 8

on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation come from the at least one driver input or the at least one active assist program; and

wherein the at least one active assist program includes an adaptive cruise control program.

15. (currently amended) ~~The vehicle control system of claim 11, wherein:~~ A vehicle control system comprising:

a driver subsystem receiving at least one driver input from a driver of the vehicle, the driver subsystem including a driver output outputting a driver output signal, the driver output signal being derived from the at least one driver input;

an active assist subsystem including an assist input receiving the driver output signal from the driver output of the driver subsystem, the active assist subsystem including at least one active assist program having at least one active input, the at least one active assist program having an on setting wherein the at least one active assist program outputs at least one active input and an off setting wherein the at least one active assist program does not output at least one active input, the at least one active assist subsystem including an assist output;

a vehicle control and implementation subsystem having a control input receiving an intended driving demand from the assist output of the active assist program; _____

wherein the intended driving demand is derived from a combination of the at least one driver input and the at least one active input if the at least one active assist program is in the on setting and if the driver of the vehicle does not overrule the at least one active assist program, otherwise the intended driving demand is derived from the at least one driver input, such that the vehicle control and implementation subsystem cannot determine if instructions for the vehicle control and implementation come from the at least one driver input or the at least one active assist program; and

wherein the at least one active assist program includes a collision mitigation program.

Applicant : Erik Coelingh et al.
Appln. No. : 10/063,951
Page : 9

16. (original) The vehicle control system of claim 11, wherein:
the intended driving demand includes a longitudinal acceleration demand.
17. (original) The vehicle control system of claim 11, wherein:
the intended driving demand includes a longitudinal velocity demand.
18. (original) The vehicle control system of claim 11, wherein:
the intended driving demand includes a yaw rate demand.
19. (original) The vehicle control system of claim 11, wherein:
the intended driving demand includes a slip angle demand.
20. (original) The vehicle control system of claim 11, wherein:
the intended driving demand includes a wheel angle demand.